

TOSHIBA

Toshiba Pocket PC e740

Model(s):

e740: PXA250 400MHz /3.5", 240x320 TFT/32MB(ROM)-64MB(RAM)/SD/CFII/Microsoft Pocket PC 2002

Product Highlights

- The Toshiba Pocket PC e740 is the industry's first personal digital assistant with integrated Wi-Fi (IEEE 802.11b) wireless communication allowing mobile professionals to remain connected to the company network and surf the Web wirelessly
- All the productivity you need in the palm of your hand, the Toshiba Pocket PC e740 includes dual integrated Secure Digital™ and Compact Flash II expansion slots and an optional second battery, perfect for long road trips
- With quick synchronization of e-mail, data files and contact information, the Toshiba Pocket PC e740 is the ultimate handheld device to quickly access vital data while in a business meeting or on the road
- A sleek and lightweight mobile presentation tool, the Toshiba Pocket PC e740 features an optional expansion pack for easy connectivity to a projector or monitor
- The Toshiba Pocket PC e740 illustrates Toshiba's commitment to the research and development of productivity device to keep the mobile workforce always connected

System Characteristics

Processor

- Intel® PXA250 processor 400MHz

Memory

- Main memory: 64MB SDRAM
- Program memory: 32MB CMOS Flash ROM

Graphics/Video

- 3.5" TFT color reflective display; 240 x 320 (portrait) resolution (16 bit)
- Front light fluorescent lamp
- 65,536 (64K) colors: 5 step brightness control (by Software)
- ATI Graphics Controller; 384KB internal video memory
- Support Resolution/Color (VGA): SVGA 800 x 600 (RGB (Monitor) via Expansion Pack)

Input Devices

- **Touch Panel:** Analog resistance sensitive system touch panel; 1024 x 1024 dots
- **Controls/Buttons:** 5-way navigation button; 4 application keys- Calendar, Contacts, Task, Menu; 3 function navigator (Toshiba Scroller) for Up, Down and Action; Reset switch; Voice record button; Power on/off button; Battery on/off switch; RF Power on/off switch, Stylus pen

Expandability

- 1 Type II CF Card Slot (3.3V)
- 1 SD (Secure Digital) card slot (3.3V)

Communications

- Integrated Wi-Fi (IEEE 802.11b)

Ports

- RGB (Monitor) port (**via Expansion Pack**)
- Universal Serial Bus port – (**Client,Host via Expansion Pack**)
- Infrared port (115kbps)
- DC-in
- Cradle connector port (26 pins)
- Stereo headphone port

Physical Description

- Dimensions (LxWxH): 4.9" x 3.1" x 0.6"
- Weight: 6.1oz
- LED Indicators: Power Charging/Alarm; Wireless LAN Power/Linking Status

Sound

- AC-97 Codec Chip; WM9705 Sound Chip
- 16-bit stereo; 8.0, 11.025, 22.05 and 44.1KHz Sample Rate
- Full Duplex Record and Playback
- Software Volume Control
- Built-in Microphone and Built-in Speaker
- Stereo Headphone jack

Power Supply

- **AC Adapter:** 5V/2A DC output; 100-240V input voltage, 50/60Hz frequency

- **Battery Pack:** Rechargeable, replaceable Advanced Lithium-Ion (Li-Ion) battery; 3.7V x 1000mAh
Rechargeable, replaceable back-up battery; 17mAh
- **Battery Saver:** Stand by; Display Auto Off

Battery life may vary depending on applications, power management settings and features utilized. Recharge time varies depending on usage.

Operating System

- **Microsoft® Pocket PC 2002**

Additional Software

- Pocket Word
- Pocket Excel
- Pocket Outlook®
- Pocket Internet Explorer
- Microsoft® Reader 2.0 for Pocket PC
- Microsoft® Windows® Media™ Player 8 for Pocket PC
- File Explorer
- MSN® Messenger
- Microsoft® Transcriber
- Microsoft® Active Sync® 3.5
- IA Screen Mirror for ATI
- IA Presenter for ATI
- Microsoft® Outlook 2002
- Adobe® Acrobat® Reader® for Pocket PC

Warranty

- 1 year parts, labor and battery
- 90-day limited warranty on operating system and applications

Environmental Specifications

- **Temperature:** Operating- 5° to 35°C (41° to 95°F); Non-operating- -20° to 65°C (-4° to 149°F)
- **Thermal gradient:** Operating- 15°C per hour maximum; Non-operating- 20°C per hour maximum
- **Relative Humidity:** Operating- 20% to 80% non-condensing; Non-operating- 10% to 95% on-condensing
- **Altitude (relative to sea level):** Operating- -60 to 3000 meters; Non-operating- -60 to 10,000 meters
- **Shock:** Operating- 10G; Non-operating- 60G
- **Vibration:** Operating- 0.5G; Non-operating- 1.0G

Accessories

PA3185U-1ETC	USB Client Cable
PA3183U-1ACA	10W AC Adapter
PA3186U-1DST	USB Cradle
PA3182U-1ETC	Stylus Pen (3-Pack)
PA3197U-1BRL	Toshiba High Capacity Battery
PA3187U-1BRS	Toshiba Primary Battery
PA3188U-1PRP	Toshiba Expansion Pack
PA3172U-1BTM	Bluetooth SD (Secure Digital) Card
PA1301U-1PCS	Leather Case
PA1302U-1PMS	Screen Overlays

Product/Part Numbers/UPC

PA3170U-3P05	Pocket PC e740
--------------	----------------

Box contents: Toshiba Pocket PC e740, USB Cradle, 10W AC Adapter, 1-Stylus, Soft Slip Case, Quick Start Card and Warranty Card.